07 · FRACTURING

Electric Drive Fracturing Equipment

Power, control, motors and frac pumps in one complete set.



105–140 MPa	600–4500 kW	3037 L/min	6
MAX OPERATING PRESSURE	MOTOR POWER	MAX DISPLACEMENT	MODELS

Based on years of experience in electrical transmission and automation control in the oil industry, Hande integrates power management, electrical control, motors and fracturing pumps into a complete set of electric drive fracturing equipment.

PRODUCT ADVANTAGES

- Independent R&D
- Strong adaptability
- High cost-effectiveness
- Integrated production
- One-stop service

ELECTRICAL CONTROL ROOM

TECHNICAL PARAMETERS

Parameter	HDYL-600	HDYL-1000	HDYL-2000	HDYL-2500	HDYL-2800	HDYL-6000
Max operating pressure (MPa)	105	105	105	105	140	140
Max displacement (L/min)	1170	1950	1820	3037	3037	2600
Plunger diameter (in)	2.75/3/3.5/4	2.75/3/3.5/4	4/4.5/5	4/4.5/5	3.75/4/4.5/5	4.5/5/5.5
Plunger pump model	HD600	HD1000	HD2000	HD2500	HD2800	HD6000
Frac skid size (mm)	5000×2450×2600	5000×2450×2600	5500×2450×2600	6000×2450×2600	3100×2500×3000 / 6000×2450×2600	7500×2600×2800
Frac skid weight (t)	10	12	18	20	20	36
Motor power (kW)	600	800	1600	1800	2000	4500
Control room size (mm)	6000×2900×3000	6000×2900×3000	9500×2900×3000	9500×2900×3000	9500×2900×3000	10000×2800×3000
Control room weight (t)	12	13	16	17	17	32
Transmission	Variable frequency	DC / variable frequency	Variable frequency	Variable frequency	Variable frequency	Variable frequency

Tell us the rig.

Service across China's major oil fields and 30+ countries.

sales@han-de.com

www.han-de.com